

Integ R Series

The Power Reader

4G Module



4G Module

Hardware Parameter	
SIM Card Type	Nano SIM Card
Data Transmission Interval	1min(Variable)
Data Access	Cloud Server
Working Voltage	DC 5V
Working Current	150mA (550mA Peak)
Display	LED
Application Parameter	
Inverter Communication	Modbus RTU (RS 485)
Server Communication	Modbus TCP
Serial Port Communication Rate	115200 bps
CN Version	LTE FDD: B1/B3/B5/B8; LTE TDD: B34/B38/B39/B40/B41; GSM: B3/B8
EU Version	LTE FDD: B1/B3/B5/B7/B8/B20/B28; LTE TDD: B38/B40/B41; GSM: B2/B3/B5/B8
AU Version	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28/B66; LTE TDD: B38/B40/B41; GSM: B2/B3/B5/B8
General Parameter	
Dimensions	110.5mm*51mm*35mm
Weight	60.5g
Operating Temperature	-30~+65°C
Operating Humidity	0%-90% Relative Humidity, No Condensation
Storage Temperature	-40~+85°C
Storage Humidity	< 40%
Protection Degree	IP65(with Inverter)
Warranty	2 Years